

YXD55P-AWM(T)

Indoor
Floor Standing
LCD Digital Signage
(Touch Optional)



Shenzhen Yaxunda LCD Display Equipment Co.,Ltd

Panel Size	55inch
Model No.	YXD55P-AWM (T)

LCD specification

Active Area	680*1210mm
Aspect Ratio	9:16
Contrast ratio	4000:1
Brightness	350cd/m2
Resolution	1080*1920
Pixel Pitch	0.63 * 0.63
Color	16.7M
Viewing angle	178/178
LED backlight	Yes
Response time	6ms
Touch screen	Optional (Capacitive Touch)
Life	50000(hrs)

Power

Power supply	AC110-240V 50-60Hz
Power	115W
Operation temperature	0 +50℃ (no condensation)
Operation humidity	10%-95% (no condensation)

hardware Specification

CPU	Android RK3288
Memory	2GB
Nand flash	8GB
Storage port	USB, SD card, SATA port hard disk storage
OS	Android 5.1
WiFi	Yes, inbuild WiFi(802.11b/g/n);
4G	Optional to add(including GPS, Bluetooth)
Output	HDMI, VGA, LVDS
Input	USB*4, Micro SD*1, RJ45*1, SATA*1, PCI*1, Audiox1

System function

Support video	MPEG1/MPEG2/MPEG4/AVI/VOB/MOV/WMV/DIVX/RM/RMVB, support super HD 2160P video
Support picture	JPG/JPEG/PNG/BMP

Shenzhen Yaxunda LCD Display Equipment Co.,Ltd

Support TXT	TXT/WORD/EXCEL/PDF
Support Website	HTML/ASP/JSP/PHP
Support RSS	Internet RSS title and text, flip over/page turning
Long-distance control	monitoring the terminal display image in real time
Long-distance wake up	Wake up the off terminal end by the current network
Timer	Set time on/off auto
Image rotate	support 90° ,180° ,270° image rotate
Software upgrade	Support upgrade software by USB disk

Capacitive Touch (Optional)


Touch points	10 points
Touch type	Capacitive Touch
Light transmittance	>90%
Resolution	4096*4096
Response time	<10ms

Structure

Glass	4mm Tempered Glass
Color	Black
Speaker	2 built-in speakers (10w)
Conternt Management Software	Freely provided for Android version
Install method	Floor Standing
Net Weight	57KG
Dimension	1960*747*21 (mm)
Packing method	Each one packed into a honeycomb carton, then <4 pcs, put into a wooden case; >4pcs, put on a pallet.
Android interface	USB*4, RJ45, Power Connector, Power Button
Internal Interface	RJ 45*2, Audio Out, Audio In, AV, VGA In, DVI In, HDMI In*2, USB

Draw

Shenzhen Yaxunda LCD Display Equipment Co.,Ltd



Pictures



Shenzhen Yaxunda LCD Display Equipment Co.,Ltd



Packing Pictures

Honeycomb Carton:(free)

Wooden Case (need to charge the cost)

Pallet: (free)

