

Product characteristics	picture; Intelligen Multiple H Intelligen energy and Intelligen	filtering and noise reduction, progressive scanning, real and delicate t screen protection function, anti burn; D signal interfaces, strong compatibility; t backlight brightness control, improve the visual effect of the image, save power. t temperature control and heat dissipation / heating system ensures stable of the machine in the best environment.	
Broadcasting system	vertically. The screen area subtitle, mixed It supports prostage timing of Different users Adopt distribut It supports And list, remote more The brightness environment. Support all kingstribut It support all kingstribut It support all kingstribut It support all kingstributes.	rea can be arranged and layered freely, and can be played horizontally and a can be divided freely, and pictures, audio, video, webpage, clock, date, d material editing can be combined. Ogram and playlist preview, real-time monitoring of playing picture, multinary off setting, and automatic reset. So can set different operation permissions. Sted management, support remote or local control. Idroid mobile phone or tablet end-to-end broadcast terminal to send program conitoring and timing on-off function. Of the screen is automatically adjusted according to the surrounding and of regular audio / video, and office documents. WiFi, RJ45, 4G networks.	
Product name		Specification parameter	
Display	LCD: 49 Inch 1920*1080/3840* Display Area: 1 brightness: 500 backlight: LED	1073*604 Point Distance: 0.63 * 0.63 contrast: 5000:1 O CDM2 Response Time: 6ms Angle: Horizontal / Vertical: 178	
Main board plan	Motherboard: rk3288 quad core main frequency 2.0GHz memory: 2GB Built in storage: EMMC 8g (expandable 64g) operating system: Android 6.0		
Interface	POWER	DC 12V AUDIO USB OTG USB TF/SIM RJ45 UBOOT	
,	Manual	, remote control, warranty card, certificate of conformity, power cord	
parts			
parts	Product architecture	Hardware Iron Plate + Paint Process + Aluminium Alloy frame	
parts	Product architecture Installation		
parts product mix	Product architecture	Hardware Iron Plate + Paint Process + Aluminium Alloy frame	
	Product architecture Installation mode Protective	Hardware Iron Plate + Paint Process + Aluminium Alloy frame Horizontal Wall	
	Product architecture Installation mode Protective glass weight Product size	Hardware Iron Plate + Paint Process + Aluminium Alloy frame Horizontal Wall None	
	Product architecture Installation mode Protective glass weight	Hardware Iron Plate + Paint Process + Aluminium Alloy frame Horizontal Wall None 38.15kg	
	Product architecture Installation mode Protective glass weight Product size Packing	Hardware Iron Plate + Paint Process + Aluminium Alloy frame Horizontal Wall None 38.15kg 1086*617*62 (mm)	
	Product architecture Installation mode Protective glass weight Product size Packing dimensions Brightness	Hardware Iron Plate + Paint Process + Aluminium Alloy frame Horizontal Wall None 38.15kg 1086*617*62 (mm) 1215*750*260 (mm)	

Working parameters	Remote monitoringWa terproof requirement	None
	work environment	Operating temperature: 0 ° C to + 45 ° c operating humidity: 5% to 90%
	Power Supply	AC110~240V 60HZ
	power	120W