

| Product<br>characteristics | 3D digital filtering and noise reduction, progressive scanning, real and<br>delicate picture;<br>Intelligent screen protection function, anti burn;<br>Multiple HD signal interfaces, strong compatibility;<br>Intelligent backlight brightness control, improve the visual effect of the<br>image, save energy and power.<br>Intelligent temperature control and heat dissipation / heating system ensures<br>stable operation of the machine in the best environment.   |  |  |
|----------------------------|---|--|--|
| Broadcasting<br>system     | Each playing area can be arranged and layered freely, and can be played<br>horizontally and vertically.<br>The screen area can be divided freely, and pictures, audio, video, webpage,<br>clock, date, subtitle, mixed material editing can be combined.<br>It supports program and playlist preview, real-time monitoring of playing<br>picture, multi-stage timing on / off setting, and automatic reset.<br>Different users can set different operation permissions.<br>Adopt distributed management, support remote or local control.<br>It supports Android mobile phone or tablet end-to-end broadcast terminal to<br>send program list, remote monitoring and timing on-off function.<br>The brightness of the screen is automatically adjusted according to the<br>surrounding environment.<br>Support all kinds of regular audio / video, and office documents.<br>Support wired, WiFi, RJ45, 4G networks. |  |  |
| Product name               | Specification parameter   |  |  |
| Display                    | LCD: 55"TFT screen,<br>Resolution: 1920 * 1080screen ratio: 16:9Display Area: 1210 * 680<br>Brightness: 500 CDM2Point Distance: 0.63 * 0.63<br>Response Time: 6mscontrast: 4000:1<br>Angle: Horizontal /Vertical: 178Point Distance: 0.63 * 0.63<br>Response Time: 6mscontrast: 4000:1<br>Angle: Horizontal /   |  |  |

| Main board plan    | Motherboard: rk3288 quad core main frequency 2.0GHz<br>memory: 2GB<br>Built in storage: EMMC 8g (expandable 64g)<br>operating system: Android6.0 |  |  |
|--------------------|--|--|--|
| Interface          | POWER  | DC 12V AUDIO USB OTG USB TF/SIM RJ45 UB00T   |  |
| parts              | Manual, remote control, warranty card, certificate of conformity, power cord   |  |  |
| product mix        | Product<br>architect   | Hardware Iron Plate + Paint Process+Aluminium Alloy frame                            |  |
|                    | Installat<br>ion mode  | Floor type   |  |
|                    | Protectiv<br>e glass   | 4MM STEEL  |  |
|                    | weight   | 56kg   |  |
|                    | Product<br>size  | 1895*747*48 (mm)   |  |
|                    | Packing<br>dimension<br>s  | 1975*827*128 (mm)  |  |
| Working parameters | Brightnes<br>s control   |  |  |
|                    | temperatu<br>re  |  |  |
|                    | work<br>environme  | Operating temperature: 0 $^\circ$ C to + 45 $^\circ$ c operating humidity: 5% to 90% |  |
|                    | Power<br>Supply  | AC110~240V 60HZ  |  |
|                    | power  | 120W   |  |