

# YXD75S-WB

Outdoor Waterproof  
Dual screen Floor standing  
LCD advertising display



Trade Condition	
Model No.	YXD75S-WB
Panel Specification(2 SCREEN)	
Panel Size	75" (16:9)
Resolution	3840x2160
Pixel Pitch	0.4875x0.4875
Contrast ratio	1400:1

# Shenzhen Yaxunda LCD Display Equipment Co.,Ltd

Active area	1650.24 x 928.26
Brightness	3000cd/m <sup>2</sup>
Viewing angle	89/89/89/89
Camera	Yes
<b>Android Specification</b>	
Operating System	Android
CPU	<b>Android A3288</b>
Memory	<b>2GB</b>
Nand flash	<b>8GB</b>
Storage port	USB, SD card, SATA port hard disk storage
OS	Android 5.1
WiFi	Yes, inbuild WiFi(802.11b/g/n); 3G/GPS/Bluetooth(optional)
Output	HDMI, LVDS
Other ports	USB x 2, SD x 1, RJ45 x 1, HDMI out x 1, Audio out x 1
Speaker	inbuild 2 speakers (2*10W/pc)
<b>System function</b>	
Support video	MPEG1/MPEG2/MPEG4/AVI/VOB/MOV/WMV/DIVX/RM/RMVB, support super HD 2160P video
Support picture	JPG/JPEG/ PNG/BMP
Support Flash	SWF/FLV/F4V
Support TXT	TXT/WORD/EXCEL/PDF
Support Website	HTML/ASP/JSP/PHP
Support RSS	Internet RSS title and text, flip over/page turning
Long-distance control	Monitoring the terminal display image in real time
Long-distance wake up	Wake up the off terminal end by the current network
Timer	Set time on/off auto
Image rotate	Support 90° ,180° ,270° image rotate
Display zone	Support more than 30 individual display zones
Software upgrade	Support upgrade software by LAN or SD card
<b>Environment</b>	
Operation temperature	-20 +55°C ( no condensation)
operation humidity	5%-90% ( no condensation)
<b>Hardware</b>	
Surface	Metal + tempered glass
Unique fan system	When the external environment is high, the refrigeration system is activated automatically When the external environment is low, the heating system is started automatically

# Shenzhen Yaxunda LCD Display Equipment Co.,Ltd

<b>Metal bracket</b>	Yes
<b>Power protection system</b>	Yes
<b>Detailed</b>	
<b>Shell</b>	Sheet metal shell with 1.5mm SGCC galvanized steel, the inner coating of zinc-rich powder coating, surface spray DuPont outdoor plastic powder protection, the useful life is 10 years.
<b>Tempered Explosion-proof Glass</b>	6mmAR anti-reflective glass, imported glass original film, AR anti-glare coating; Light transmittance of 97%, reflectance of 3%; Isolation of 99% of the sun's ultraviolet rays, 52% solar heat isolation;
<b>LCD panel</b>	Outdoor special highlight LCD screen; LED direct type backlight, brightness 3000cd / m2, the sun readable; Screen resolution UHD 3840 * 2160; Automatic sensor, according to the ambient light to adjust the screen brightness, energy saving, reduce light pollution;
<b>Electronic control system</b>	Leakage protection switch, leakage protection, overvoltage protection; Microcomputer timer switch, sub-time control of the machine start and stop hours; Lightning protection, lightning protection level C-class, to prevent lightning induction instantaneous; Ming Wei, Taiwan's industrial-grade power supply, power supply is stable and reliable;
<b>Temperature control system</b>	Air condition integrated temperature control, charged heating, to meet the -20- +55 degrees outdoor environment, the display is not black, the whole machine work; Automatic temperature, automatically adjust the speed, energy saving, extended life; Efficient multi-layer filtration system, isolated harmful dust into the machine, the whole degree of protection to IP55;
<b>Has completed the test</b>	Spray waterproof test; High and low temperature test; Solar radiation test Machine aging test;
<b>Picture</b>	

# Shenzhen Yaxunda LCD Display Equipment Co.,Ltd

Size (75inch)

