

YXD65S-DWL

Outdoor Waterproof
Wall mount
LCD advertising display



Trade Condition	
Model No.	YXD65S-DWL
Panel Specification	
Panel Size	65"(16:9)
Resolution	3840*2160
Pixel Pitch	0.42975x0.42975


Shenzhen Yaxunda LCD Display Equipment Co.,Ltd

Contrast ratio	5000:1
Active area	1428*803
Brightness	3000cd/m2
Viewing angle	89/89/89/89
Android Specification (option)	
Operating System	Android
CPU	Android RK3288, 4-core
Memory	2GB
Nand flash	16GB
Storage port	USB, SD card, SATA port hard disk storage
OS	Android 7.1
WiFi	Yes, inbuild WiFi(802.11b/g/n); 3G/GPS/Bluetooth(optional)
Output	HDMI, LVDS
Other ports	USB x 2, SD x 1, RJ45 x 1, HDMI out x 1,Audio out x 1
Speaker	yes
System function	
Support video	MPEG1/MPEG2/MPEG4/AVI/VOB/MOV/WMV/DIVX/RM/RMVB, support super HD 2160P video
Support picture	JPG/JPEG/PNG/BMP
Support Flash	Flash 11, SWF/FLV/F4V
Support TXT	TXT/WORD/EXCEL/PDF
Support Website	HTML/ASP/JSP/PHP
Support RSS	Internet RSS title and text, flip over/page turning
Long-distance control	monitoring the terminal display image in real time
Long-distance wake up	Wake up the off terminal end by the current network
Timer	Set time on/off auto
Image rotate	support 90°,180°,270° image rotate
Display zone	Support more than 30 individual display zones
Software upgrade	Support upgrade software by LAN or SD card
Environment	
Operation temperature	-20 +50℃ (no condensation)
operation humidity	5%-90% (no condensation)
Detailed	
Shell	Sheet metal shell with 1.5mm SGCC galvanized steel, the inner coating of zinc-rich powder coating, surface spray DuPont outdoor plastic powder protection, the useful life is 10 years.
Tempered Explosion-proof Glass	6mmAR anti-reflective glass, imported glass original film, AR anti-glare coating; Light transmittance of 97%, reflectance of 3%; Isolation of 99% of the sun's ultraviolet rays, 52% solar heat isolation;

Shenzhen Yaxunda LCD Display Equipment Co.,Ltd


LCD panel	Outdoor special highlight LCD screen; LED direct type backlight, brightness 3000cd / m2, the sun readable; Screen resolution HD 3840*2160; Automatic sensor, according to the ambient light to adjust the screen brightness, energy saving, reduce light pollution;
Electronic control system	Leakage protection switch, leakage protection, overvoltage protection; Microcomputer timer switch, sub-time control of the machine start and stop hours; Lightning protection, lightning protection level C-class, to prevent lightning induction instantaneous; Ming Wei, Taiwan's industrial-grade power supply, power supply is stable and reliable;
Temperature control system	Smart fan integrated temperature control, charged heating, to meet the -20- +50 degrees outdoor environment, the display is not black, the whole machine work; Adopt imported centrifugal / axial fan, supporting fan speed board, automatic temperature, automatically adjust the fan speed, energy saving, extended fan life; Efficient multi-layer filtration system, isolated harmful dust into the machine, the whole degree of protection to IP55;
Has completed the test	Spray waterproof test; High and low temperature test; Solar radiation test Machine aging test;

Picture


Hydraulic support	
--------------------------	--

Shenzhen Yaxunda LCD Display Equipment Co.,Ltd

Inside structure




Timer



Shenzhen Yaxunda LCD Display Equipment Co.,Ltd

1. Main board
2. Temperature control board
3. Power board



- 1.Fan
- 2.Warming system
- 3.Filter layer
- 4.Rainwater backflow system

