

# YXD75S-DWP

Outdoor Waterproof  
Floor standing  
LCD advertising display



| Trade Condition     |               |
|---------------------|---------------|
| Model No.           | YXD75S-DWP    |
| Panel Specification |               |
| Panel Size          | 75" (16:9)    |
| Resolution          | 3840x2160     |
| Pixel Pitch         | 0.4875x0.4875 |
| Contrast ratio      | 1400:1        |

# Shenzhen Yaxunda LCD Display Equipment Co.,Ltd

|                              |   |
|------------------------------|---|
| Active area                  | 1650.24 x 928.26  |
| Brightness                   | 3000cd/m <sup>2</sup>   |
| Viewing angle                | 89/89/89/89   |
| Camera                       | Yes   |
| <b>Android Specification</b> |   |
| Operating System             | Android   |
| CPU                          | Android RK3288  |
| Memory                       | 2GB   |
| Nand flash                   | 16GB  |
| Storage port                 | USB, SD card, SATA port hard disk storage   |
| OS                           | Android 7.1   |
| WiFi                         | Yes, inbuild WiFi (802.11b/g/n); 3G/GPS/Bluetooth(optional)   |
| Output                       | HDMI, LVDS  |
| Other ports                  | USB x 2, SD x 1, RJ45 x 1, HDMI out x 1, Audio out x 1  |
| <b>System function</b>       |   |
| Support video                | MPEG1/MPEG2/MPEG4/AVI/VOB/MOV/WMV/DIVX/RM/RMVB, support super HD 2160P video  |
| Support picture              | JPG/JPEG/ PNG/BMP   |
| Support Flash                | SWF/FLV/F4V   |
| Support TXT                  | TXT/WORD/EXCEL/PDF  |
| Support Website              | HTML/ASP/JSP/PHP  |
| Support RSS                  | Internet RSS title and text, flip over/page turning   |
| Long-distance control        | Monitoring the terminal display image in real time  |
| Long-distance wake up        | Wake up the off terminal end by the current network   |
| Timer                        | Set time on/off auto  |
| Image rotate                 | Support 90° ,180° ,270° image rotate  |
| Display zone                 | Support more than 30 individual display zones   |
| Software upgrade             | Support upgrade software by LAN or SD card  |
| <b>Environment</b>           |   |
| Operation temperature        | -20°C+50°C ( no condensation)   |
| operation humidity           | 5%-90% ( no condensation)   |
| <b>Hardware</b>              |   |
| Surface                      | Metal + tempered glass  |
| Unique fan system            | When the external environment is high, the refrigeration system is activated automatically<br>When the external environment is low, the heating system is started automatically |

# Shenzhen Yaxunda LCD Display Equipment Co.,Ltd

|                                       |   |
|---------------------------------------|---|
| <b>Metal bracket</b>                  | Yes   |
| <b>Power protection system</b>        | Yes   |
| <b>Detailed</b>                       |   |
| <b>Shell</b>                          | Sheet metal shell with 1.5mm SGCC galvanized steel, the inner coating of zinc-rich powder coating, surface spray DuPont outdoor plastic powder protection, the useful life is 10 years.   |
| <b>Tempered Explosion-proof Glass</b> | 6mmAR anti-reflective glass, imported glass original film, AR anti-glare coating;<br>Light transmittance of 97%, reflectance of 3%;<br>Isolation of 99% of the sun's ultraviolet rays, 52% solar heat isolation;  |
| <b>LCD panel</b>                      | Outdoor special highlight LCD screen;<br>LED direct type backlight, brightness 3000cd / m2, the sun readable;<br>Screen resolution UHD 3840 * 2160;<br>Automatic sensor, according to the ambient light to adjust the screen brightness, energy saving, reduce light pollution;   |
| <b>Electronic control system</b>      | Leakage protection switch, leakage protection, overvoltage protection;<br>Microcomputer timer switch, sub-time control of the machine start and stop hours;<br>Lightning protection, lightning protection level C-class, to prevent lightning induction instantaneous;<br>Ming Wei, Taiwan's industrial-grade power supply, power supply is stable and reliable;                                    |
| <b>Temperature control system</b>     | Smart AC / fans cooling integrated temperature control, charged heating, to meet the -20- +50 degrees outdoor environment, the display is not black, the whole machine work;<br>Automatic temperature, automatically adjust the speed, energy saving, extended AC life;<br>Efficient multi-layer filtration system, isolated harmful dust into the machine, the whole degree of protection to IP55; |
| <b>Has completed the test</b>         | Spray waterproof test;<br>High and low temperature test;<br>Solar radiation test<br>Machine aging test;   |