


YXD27P-WZDT

Touchless self payment kiosk

1. PCAP touch screen
2. 27inch FHD screen
3. Thermal printer- easy to change paper
4. QR code scanner
5. POS /NFC to option
6. Anti-peeping mirror
7. Android / Windows 10 to option



Panel Specifications			
LCD Size	27inch	Area	597.888×336.312 mm
Resolution	1920*1080	View Angle	178/178/178/178
Display Ratio	9:16	Response Time	6ms
Brightness (nits)	250cd/m2	Life (hrs)	50000
Contrast	1000:1	Power Input	AC 100-240V
Input ports			
USB 2.0	x2	SD	x1
LAN	X1	SIM card reader	X1 (for 4G use)
Operate system's of kiosk specification			
Operate System	Android 5.1/7.1	RAM	2GB
CPU	Rockchip RK3288 quad-core ARM Cortex-A17	ROM	8GB
Supported Media formats			
Video	MPEG1/MPEG2/MPEG4/AVI/VOB/MOV/WMV/DIVX/RM/RMVB, support super HD 2160P video		
Image	JPG/JPEG/PNG/BMP		
Audio	MP3/WMA/AAC etc		
Scrolling text	TXT/WORD/EXCEL/PDF		
Functions			
Rolling subtitles	Display the subtitles at the bottom of screen with the video and picture	Software Update	Software update
Power Memory	Support program replaying from the setting time before the power failure	Display Mode	Support Portrait display mode
Split Screen	Support 1080p video, 1080p picture, picture, video and subtitles split-screen function.	Play mode	Repeat all, single repeat, order play
Anti-peeping	Yes	Print paper	Yes

Scan code	Yes, bar code & QR code	Option support	NFC/ POS machine
Thermal printer			
Printing method	Line thermal printing	Resolution	203dpi
Printing speed	100mm/s (max)	Cut way	Full cut/half cut
Printing width	384dots/line (48mm)	Printing length	100KM
Paper width/thickness	58 ± 0.5 mm / 56~105µm	Cutter life	1 million times
The maximum diameter of the paper roll	<= 50mm	character	FONT A 12*24 points FONT B 9*17 points GB18030 Simplified Chinese 24*24 points GB2312 Simplified Chinese 16*16 points
Loading way	Easy paper loading	Environmental	operating temperature -10~50℃ (no condensation) Operating humidity 20%~85%RH (85%RH at 40℃)
QR code scanner			
Trigger mode	automatic induction, continuous reading, command trigger	Parameter setting method	Scan QR code to set parameters or host command settings
Prompt method	Connect buzzer, LED indicator	Scan angle	Inclination angle ±55°, rotation 360°
Decoding type (bar code)	UPC-A, UPC-E, EAN-13, ISBN10, ISBN13, EAN-8, CODE39, CODE 11, CODE 93, CODE128, INTERLEAVED25, INDUSTRIAL25, MATRIX25, S25, CODE 32, TRIOPTIC39, GS1_128, CODABAR, MSI, China postal code, TELEDEN, RSS, GS1_DATABAR, GS1_DATABAR_LIM, GS1_DATABAR_EXP;	Decoding type (QR code)	QR, MICROQR, PDF417,, Data Matrix
Minimum resolution	7mil, 1mil = 0.0254mm 5mil, 1mil = 0.0254mm	Reading distance QR	4 cm~ 20cm
Working temperature	-30~60℃	Humidity	5%~95% (no condensation)
Option			
NFC	Yes	POS machine	Yes
Floor stand	Yes	Adjust high	0.7-1.33meters
VESA Support	75*75, 100*100/200/100, 150*100, 100*200, 200*200	Package dimension	90*35*10cm
Max support weight	35kgs	Package G.W.	12KGS