Asianda® 43inch Indoor Double Screens Hanging LCD Display--Android Version

Product Characteristics





Application



Drawing



- 1 3d digital filter noise reduction, line-by-line scanning, the screen is true and delicate
- 2 Smart screen protection function, prevent Burns

3	Various high definition	signal interface, strong compatibility		
4	Intelligent backlight brightness control, improve the visual effect of image, save energy and save electricity			
5	The intelligent temperature control cooling / heating system ensures the machine to work stably in the best environment.			
Display Screen				
6	LCD Screen	43 Inch TFT		
7	Brightness	700/300cd/m2		
8	Display Area	940×529mm		
9	Resolution	1920*1080P		
10	Screen Ratio	16:9		
11	View angle	178°(H)/178°(V)		
12	Contrast ratio	1200:1		
13	Response time	6ms		
14	Lifespan	50000~60000h		
15	Backlight	LED backlight		
Motherboard Scheme				
16	Motherboard	RK3288 quad-core, 2.0		
17	Memory	RAM: 2G; ROM: 8G		
18	OS	Android 7.1		
19	WiFi	Yes, (802.11b/g/n) 4G module		
Android Interface	POWER	DC 12V AUDIO USB OTG USB TF/SIM RJ45 UBOOT		
Accessories	Manual,	remote control, warranty card, certificate of conformity, Power Cord		
Electronic Control				
20	Timer	Can Be set by day, week, month custom switch machine		
21	Leakage Protector	When the leakage current is greater than 30MA, the circuit should be disconnected to protect the human body		

22	Lightning arrester	Self-check outdoor lightning strike 40kA surge current, play a 3-level lightning protection effect, to protect the safety of equipment		
23	Switching power supply	Using industrial-grade power supply, 365 days stable throughout the year, continuous voltage output		
24	Waterproof Horn	Waterproof high quality 10W speaker, sound quality lifelike, Sound Sense Stereo		
Product structure				
25	Product architecture	1.5 mm galvanized sheet, sprayed Aksu outdoor powder, outdoor anti-corrosion for more than 7 years		
26	Dust proof design	The shell structure design waterproof trough and in and out the wind hole waterproof labyrinth, meets the IP55 protection grade		
27	Anti-theft design	The Base / Hanger is designed with an internal lock to prevent the machine from being moved by removing screws from the outside, which is really safe against theft		
28	Waterproof design	The air inlet and outlet are designed with special dust-proof filter (medium and high efficiency dust-proof filter) to filter the fine dust in the air and prevent mosquitoes and insects from entering the machine		
29	Installation mode	Hanging type		
30	Protective Glass	6 mm high transmittance toughened glass or AR anti-glare toughened glass, light transmittance \geq 97%, high transmittance		
		Operating parameter		
31	Working Environment	Working Temperature: -20°C to + 55 °C working humidity: 5% to 90%		
32	Power supply	AC110~240V 60HZ		
		Playback system		
33	Each playing area can b	be arranged and layered freely, and can be played on horizontal and vertical screens		
34	Screen Area Free Segmentation, composable picture, audio, video, web page, clock, date, caption, mixed material editing			
35	Support Program and broadcast table preview, real-time monitoring playback screen, multi-stage timing switch settings, automatic reset			
	Different users can set	different permissions		
36	Different users can set of			
36 		gement, support remote or local control		

39	Screen brightness can be adjusted automatically according to the surrounding environment
40	Screen brightness can be adjusted automatically according to the surrounding environment
41	Supports a variety of general audio / Video, and office documents
42	Support cable, Wifi, 4G network