

Shenzhen Yaxunda LCD Display Equipment Co., Ltd

Model no: YXD55S-DWX

55-inch outdoor floor standing display

Product Image








Product size


1950(H)*770(W)*140(T)mm


Aplication Pictures





Asianda®





Product Characteristics				
1	Fully fit screen technology.			
2	Ultra-large screen-to-body ratio 96%;			
3	Protection grade IP55,Explosion-proof grade IK10;			
4	Industrial-grade bright screen and high temperature resistance;			
5	Military superconducting uniform temperature technology which can dissipates heat quickly.			
Display Screen				
6	LCD Screen	55 Inch TFT		
7	Brightness	3000 cd/m ²		
8	Resolution	1920 * 1080		
9	Display Area	1210*680mm		
10	Contrast ratio	3000:1		
11	Screen ratio	16:9		
12	Response time	6ms		
13	Lifespan	50000~60000h		
14	Backlight	LED backlight		
15	Point Distance	0.63*0.63		
16	View angle	178°(H)/178°(V)		
17	Display color	16.7M		
Motherboard Scheme				
18	Motherboard	RK3288 quad-core, 2.0 Ghz Ram: 2 GB		
19	Build-in Storage	EMMC 8G expandable 64G		
20	Operating System	Android7.1		
Android Interface	POWER DC 12V	AUDIO USB OTG USB TF/SIM RJ45 UBOOT		
Accessories	Manual, remote control, warranty card, certificate of conformity, Power Cord			
Product Structure				

	1	T	
21	Product architecture	Hardware shell + lacquer process + aluminum alloy border	
22	Installation mode	Floor type	
23	Protective Glass	6 mm toughened glass	
24	Display mode	Horizontal screen / vertical screen, full screen / arbitrary	
25	Waterproof Level	IP66	
Heat dissipation	Through-air cooling system	Low temperature self-starting heating module	
		The temperature of self-checking probe can control the rotation speed of the fan to save energy and prolong the life of the fan	
		Intelligent temperature sensing system, high temperature automatically turn off the display	
Operating parameter			
26	Working Environment	Working Temperature: -20°C to + 55 °C working humidity: 5% to 90%	
27	Power supply	AC110~240V 50/60HZ	
28	Power	300W	
Playback System			
29	Each playing area can be arranged and layered freely, and can be played on horizontal and vertical screens;		
30	Screen Area Free Segmentation, composable picture, audio, video, web page, clock, date, caption, mixed material editing;		
31	Support Program and broadcast table preview, real-time monitoring playback screen, multi-stage timing switch settings, automatic reset		
32	Different users can set different permissions; Adopt distributed management, support remote or local control		
33	Support android phone or tablet terminal to play a list of programs, remote monitoring, timing switch function		
34	Screen brightness can be adjusted automatically according to the surrounding environment		
35	Supports a variety of general audio / Video, and office documents		
36	Support cable, Wifi, 4G network.		